



## Hydraulic Hexagonal Hose Brass Plumbing Nipple Fitting , Water Screw Plumbing Fittings

Our Product Introduction

for more products please visit us on [brassbronzecasting.com](http://brassbronzecasting.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: TSTY
- Certification: ISO9001 ISO14000
- Model Number: accordingly
- Minimum Order Quantity: 1000 sets
- Price: negotiation
- Packaging Details: Suitable for shipment
- Delivery Time: 3 weeks
- Payment Terms: L/C, T/T
- Supply Ability: 300,000 tons



### Product Specification

- Materials: BRASS BRONZE
- Technic: Forging
- Packing: As Requests
- Standard: BSP
- Services: OEM ODM
- Head Code: Round
- Shape: Equal
- Name: Hydraulic Hexagonal Hose Brass Plumbing Nipple Fitting In Water
- Highlight: plumbing pipe fittings, brass plumbing fittings



### More Images



## Product Description

### hydraulic Hexagonal hose brass plumbing nipple fitting in water

1/2 Inch Push-fit Barbed Elbows. These are lead free, have all approvals, easily removable/reusable.

Brand Name	TSTY / OEM <b>available</b>
Package	1 pc in one poly bag, 10-12 pcs in one white or brown box, 100-120pcs in brown carton, OEM <b>available</b>
Payment Terms	Negotiated
Port of Departure	250kms to Ningbo Port; 500kms to Shanghai Port, inland Yiwu Port or Customized;
Place of production	The Capital of brass valves Yuhuan, Taizhou, Zhejiang, China
Production Time	OEM order 45 days of production including new moulds, Existing products only need 30 -35 days after order confirmation
Applications	Water System
Main Material	MS58; HPB57-3; HPB59-1; CW617N; CW611N; CZ132(DZR); CW602N(DZR); OEM all type OEM are <b>available</b>
Size	1/2" DN15; 3/4" DN20; 1" DN25; 1.1/4" DN32; 1.1/2" DN40; 2" DN50 are in common use, and reduced port <b>available</b>
Threaded	G (GB/T7307-2001) ; BSP (BS21-1957); BSP.F (BS-2779); BSP.T (BS-1957)

The Push-Fit connection system is really taking hold. It's the easiest way to join copper, CPVC or PEX pipe in any combination ?

with no soldering, clamps, unions or glue. Just insert the pipe and the stainless steel teeth bite down and grip tight, while a specially formulated O-ring compresses to create a perfect seal. Disassembly is just as fast using the simple disconnect tool. So fittings and valves can be easily changed and reused. They can even be rotated after assembly for easier installation in tight spaces. Get a grip on your next plumbing project.



Packing :



上海天申铜业集团  
SHANGHAI TIANSHEN COPPER GROUP

Shanghai Tianshen Copper Group Co.Ltd



[brassbronzecasting.com](http://brassbronzecasting.com)

RM 4 A-D, No. 728 Middle Xizang Road, Huangpu District, Shanghai, China